



XF-PTL19582-M95-12-VI

Specification

Optical structure	Bi-Telecentric
Magnification	0.444
Object field of view	Φ184.7mm
Image field of view	Φ82mm
Working Distance	400mm±3%
Telecentricity	<0.04°(0.06°)
Depth of field	7.3mm@F13.5
F#	F8-F111
Resolution	20.1μm@F13.5
MTF	>0.3@75lp/mm@F13.5
Distortion	<0.042%(0.061%)
Detector type:	

35film 36×24	81.1×54.1mm
2' 23×23	51.8×51.8mm
4/3' 18×13.5	40.5×30.4mm
1.1' 14.2×10.4	32.0×23.4mm
2K Linear scan 2048×10μm	64.6mm
4K Linear scan 4096×7μm	92.3mm
8K Linear scan 8192×5μm	129.2mm
8K Linear scan 8192×7μm	184.5mm
16K Linear scan 16384×5μm	

XF-PTLAAABB-C/F/P/M- (L90E)

<p>The fourth generation lens of Canrill</p> <p>Object FOV _____</p> <p>Image FOV _____</p>	<p>The camera mount (M & P mount need specify BFL)</p> <p>90° Steering option</p>
--	---

Undefined tolerance (mm)		degree	File Name		
X. X	±0.2	±30min	XF-PTL19582-M95-12-VI-外形尺寸-EN		
X. XX	±0.02		Drawing Name		
X. XXX	±0.005	Drawing Size: A3			
	Sign	Data/Ver.	Material	Ratio	Product Name
Design				1:5	
Modify1			Qty		Canrill OPTICS
Modify2			Total:	Page:	All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.